


<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>		
Code	5376	Code	5376	Code	PL-L24W/840/4P	
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4	
Line	VIBIA-Link	Date	29-05-2014	Position	Universal	
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm	
Maximum value	62.28 cd/klm	Position	C=0.00 G=0.00	Double Symmetrical		
Rectangular Luminaire	Length	300 mm	Width	500 mm	Height	160 mm
Rectangular Luminous Area	Length	280 mm	Width	480 mm	Height	0 mm
Horizontal Luminous Area	0.134400 m2	Emitting area on Plane 180°		0.000000 m2		
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°		0.000000 m2		
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°		0.032514 m2		
Symmetry Type	Double Symmetrical	Maximum Gamma Angle		90		
Measurement Distance	6.44	Measurement Flux		6000.00 lm		
Operator	Asselum T2	Source voltage		230.00 V		
Temperature	20.00 °C	Source current				
Humidity	60.00 %	Photocell		Prc		
Notes						
<b>Luminaire Lamps</b>						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
PHILIPS 2005 ILCOS FBT,G,C,FSQ	PL-L24W/840/4P	MASTER PL-L 24W/840/4P 2G11	1800.00	24.00	2	
PHILIPS 2005 ILCOS FBT,G,C,FSQ	PL-L18W/840/4P	MASTER PL-L 18W/840/4P 2G11	1200.00	18.00	2	
C.I.E.	43 74 93 100 20	D DIN 5040	A30			
F UTE	0.20 E	B NBN	BZ 5			


300mm x 500mm



C Halfplanes

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 19.62 %  
 RN 0.00 %



<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>			
Code	5376	Code	5376	Code	PL-L24W/840/4P		
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4		
Line	VIBIA-Link	Date	29-05-2014	Position	Universal		
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm		
Luminous Intensity Table cd/klm			Table 1/1				
	C 0.00	C 15.00	C 30.00	C 45.00	C 60.00	C 75.00	C 90.00
G 0.0	62.28	62.28	62.28	62.28	62.28	62.28	62.28
G 5.0	62.11	62.03	62.03	62.01	62.01	62.01	62.02
G 10.0	61.43	61.27	61.26	61.25	61.20	61.21	61.19
G 15.0	60.21	59.98	59.97	59.96	59.97	60.02	60.04
G 20.0	58.70	58.26	58.15	58.16	58.24	58.27	58.23
G 25.0	56.49	56.01	55.88	55.98	56.00	55.99	56.01
G 30.0	53.86	53.26	53.30	53.22	53.26	53.29	53.31
G 35.0	50.61	49.96	50.16	50.08	50.14	50.17	50.22
G 40.0	47.21	46.69	46.62	46.69	46.87	46.84	46.84
G 45.0	43.61	43.07	42.79	42.82	42.89	43.16	43.43
G 50.0	39.91	39.00	38.71	38.90	39.30	39.46	39.84
G 55.0	35.53	34.62	34.59	34.58	35.28	35.59	35.98
G 60.0	31.04	30.02	30.24	30.46	31.17	31.55	31.78
G 65.0	26.29	25.52	25.79	26.44	27.24	28.23	28.55
G 70.0	21.71	20.88	21.27	22.44	23.64	24.70	24.66
G 75.0	17.59	16.63	16.74	18.35	18.71	19.49	19.16
G 80.0	13.03	11.85	11.78	12.20	12.07	12.09	11.94
G 85.0	6.69	5.20	5.24	5.22	5.15	5.36	5.19
G 90.0	0.18	0.20	0.19	0.22	0.21	0.21	0.20



<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

300mm x 500mm

C Halfplanes


180.0 ————— 0.0

270.0 ————— 90.0




<b>Luminaire</b>		<b>Measur.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

300mm x 500mm



C Halfplanes

180.0 — 0.0  
 270.0 — 90.0



<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

**UGR**  
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	15.9	17.3	16.2	17.6	18.0	16.1	17.6	16.4	17.8	18.0
x=2H y=3H	17.9	19.1	18.2	19.4	20.3	18.4	19.7	18.8	20.0	20.3
x=2H y=4H	18.8	20.0	19.2	20.2	21.2	19.5	20.6	19.9	20.9	21.2
x=2H y=6H	19.7	20.8	20.1	21.1	22.0	20.3	21.3	20.6	21.7	22.0
x=2H y=8H	20.1	21.2	20.5	21.5	22.3	20.5	21.7	20.9	21.9	22.3
x=2H y=12H	20.4	21.4	20.7	21.8	22.5	20.7	21.7	21.1	22.1	22.5
x=4H y=2H	16.8	18.0	17.2	18.2	18.7	16.9	18.1	17.3	18.4	18.7
x=4H y=3H	18.9	20.0	19.3	20.3	21.2	19.5	20.5	19.8	20.8	21.2
x=4H y=4H	20.0	21.0	20.4	21.3	22.4	20.7	21.7	21.1	22.0	22.4
x=4H y=6H	21.1	21.8	21.5	22.2	23.2	21.6	22.4	22.1	22.8	23.2
x=4H y=8H	21.5	22.2	21.9	22.6	23.5	21.9	22.7	22.3	23.1	23.5
x=4H y=12H	21.8	22.5	22.3	22.9	23.7	22.2	22.9	22.6	23.2	23.7
x=8H y=4H	20.6	21.4	21.0	21.7	22.7	21.1	21.9	21.6	22.3	22.7
x=8H y=6H	21.8	22.4	22.3	22.9	23.8	22.3	22.9	22.7	23.3	23.8
x=8H y=8H	22.3	22.9	22.8	23.3	24.2	22.7	23.2	23.2	23.7	24.2
x=8H y=12H	22.7	23.1	23.2	23.6	24.4	22.9	23.4	23.5	23.9	24.4
x=12H y=4H	20.7	21.4	21.1	21.8	22.7	21.2	21.9	21.7	22.3	22.7
x=12H y=6H	22.0	22.5	22.5	22.9	23.9	22.4	23.0	22.9	23.4	23.9
x=12H y=8H	22.5	22.9	23.0	23.4	24.3	22.8	23.3	23.3	23.7	24.3

<b>Luminaire</b>				<b>Measurem.</b>				<b>Lamp</b>			
Code	5376			Code	5376			Code	PL-L24W/840/4P		
Name	Ceiling lamp 50x30 no dim			Name	Ceiling lamp 50x30 no dim			Number	4		
Line	VIBIA-Link			Date	29-05-2014			Position	Universal		
Efficiency	19.62%			Coordinate system	CG			Total Flux	6000.00 lm		

Total Flux=6000.00 Luminaire Flux=1177.13

RI	0.60	0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	10.00	20.00
DRR	0.28	0.36	0.43	0.50	0.56	0.65	0.71	0.75	0.80	0.84	0.91	0.96
RC	6	6	6	6	6	6	6	6	6	6	6	5

Zonal Flux per 1000 Lumen


Y°	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
ZF(Y)	6	23	49	80	113	145	171	190	196	196	196	196	196	196	196	196	196	196

CIE Flux Codes

43 74 93 100 20

C.I.E.	6/6/6/6/6/6/6/6/6/5
D DIN 5040	A30
F UTE	0.20 E
B NBN	BZ 5
RN	0.00000 %
BLF	1.0

LOR	19.61886 %
ULOR	0.00000 %
DLOR	19.61886 %
UFF	0.00000 %
DFF	100.00000 %
FFR	0.00000 %




Zonal Flux				
Gamma °	Flux	Sum lm	Flux [%]	Sum [%]
0°	0.00	0.00	0.00%	0.00 %
5°	1.49	1.49	0.76 %	0.76 %
10°	4.41	5.90	2.25 %	3.01 %
15°	7.19	13.09	3.67 %	6.67 %
20°	9.75	22.84	4.97 %	11.64 %
25°	11.99	34.82	6.11 %	17.75 %
30°	13.84	48.66	7.05 %	24.80 %
35°	15.24	63.89	7.77 %	32.57 %
40°	16.17	80.07	8.24 %	40.81 %
45°	16.63	96.70	8.48 %	49.29 %
50°	16.62	113.32	8.47 %	57.76 %
55°	16.15	129.47	8.23 %	65.99 %
60°	15.23	144.70	7.76 %	73.76 %
65°	14.00	158.70	7.14 %	80.89 %
70°	12.52	171.22	6.38 %	87.27 %
75°	10.65	181.87	5.43 %	92.70 %
80°	8.06	189.93	4.11 %	96.81 %
85°	4.74	194.67	2.41 %	99.22 %
90°	1.52	196.19	0.78 %	100.00 %
95°	0.00	196.19	0.00 %	100.00 %
100°	0.00	196.19	0.00 %	100.00 %
105°	0.00	196.19	0.00 %	100.00 %
110°	0.00	196.19	0.00 %	100.00 %
115°	0.00	196.19	0.00 %	100.00 %
120°	0.00	196.19	0.00 %	100.00 %
125°	0.00	196.19	0.00 %	100.00 %
130°	0.00	196.19	0.00 %	100.00 %
135°	0.00	196.19	0.00 %	100.00 %
140°	0.00	196.19	0.00 %	100.00 %
145°	0.00	196.19	0.00 %	100.00 %
150°	0.00	196.19	0.00 %	100.00 %
155°	0.00	196.19	0.00 %	100.00 %
160°	0.00	196.19	0.00 %	100.00 %
165°	0.00	196.19	0.00 %	100.00 %
170°	0.00	196.19	0.00 %	100.00 %
175°	0.00	196.19	0.00 %	100.00 %
180°	0.00	196.19	0.00 %	100.00 %

<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.72	3.45	5.17	6.90	8.62	OC	1.80	3.59	5.39	7.19	8.98
OB	1.72	3.45	5.17	6.90	8.62	OD	1.80	3.59	5.39	7.19	8.98

	0	5	15	25	35	45	55	65	75	85
OA	373.69	372.65	361.24	338.91	303.69	261.68	213.20	157.72	105.57	40.15
OB	373.69	372.65	361.24	338.91	303.69	261.68	213.20	157.72	105.57	40.15
OC	373.69	372.12	360.22	336.03	301.30	260.56	215.87	171.30	114.98	31.13
OD	373.69	372.12	360.22	336.03	301.30	260.56	215.87	171.30	114.98	31.13




H[m]	D[m]	Max lux	Med lux	Alpha=59.9°+59.9°	G=0.0	
1.00	3.45	374	73			
2.00	6.90	93	18			
3.00	10.35	42	8			
4.00	13.80	23	5			
5.00	17.24	15	3			

H[m]	D[m]	Max lux	Med lux	Beta=60.9°+60.9°	G=0.0	
1.00	3.59	374	73			
2.00	7.19	93	18			
3.00	10.78	42	8			
4.00	14.37	23	5			
5.00	17.97	15	3			

<b>Luminaire</b>		<b>Measurem.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=3.00m





<b>Luminaire</b>				<b>Measur.</b>				<b>Lamp</b>			
Code	5376			Code	5376			Code	PL-L24W/840/4P		
Name	Ceiling lamp 50x30 no dim			Name	Ceiling lamp 50x30 no dim			Number	4		
Line	VIBIA-Link			Date	29-05-2014			Position	Universal		
Efficiency	19.62%			Coordinate system	CG			Total Flux	6000.00 lm		

#### Utilizations CIE

Mounting	Direct			NormalizationNormalised								Suspension Ratio3								Standard CIE Settings							
											</																

#### Wall

K	8873	8773	8871	8771	7773	7771	7753	7553	7751	7551	7731	7331	7711	7111	5551	5531	5331	5511	5111	3331	3311	1111	0000
0.60	94	92	83	81	90	80	71	70	65	64	54	53	47	46	63	54	53	47	46	53	46	46	42
0.80	107	104	92	90	102	89	83	81	74	73	64	62	56	55	72	63	62	55	55	62	55	55	50
1.00	115	113	97	95	111	94	92	90	80	79	70	69	62	62	78	69	68	62	61	68	61	61	56
1.25	123	121	101	100	118	98	101	98	86	85	76	75	68	68	83	75	74	68	67	74	67	67	61
1.50	129	127	104	103	123	101	107	105	90	89	81	79	73	72	87	79	79	73	72	78	72	71	65
2.00	135	133	105	104	129	103	115	113	93	93	86	85	79	78	91	84	84	78	78	83	77	77	69
2.50	139	137	106	105	133	104	120	118	96	95	89	88	83	82	93	87	86	82	81	85	81	80	72
3.00	141	140	106	105	135	104	124	122	97	96	91	90	85	84	94	89	88	84	83	87	83	82	74
4.00	145	144	107	106	139	105	130	128	99	98	94	93	89	89	96	92	92	88	87	90	87	85	77
5.00	148	147	107	107	142	105	134	132	101	100	96	96	92	92	98	94	94	91	90	92	89	88	79
10.00	153	152	108	108	147	106	142	141	104	103	101	101	99	98	101	99	99	97	97	97	95	93	83
20.00	153	153	106	106	147	104	144	144	103	103	101	101	100	100	100	99	99	98	98	97	96	94	84

#### Working Pl.


K	8873	8773	8871	8771	7773	7771	7753	7553	7751	7551	7731	7331	7711	7111	5551	5531	5331	5511	5111	3331	3311	1111	0000
0.60	113	110	105	104	109	102	86	84	82	81	69	68	59	59	80	68	68	59	59	67	59	59	55
0.80	134	131	123	121	128	119	105	103	100	99	86	85	75	75	97	85	84	75	75	84	75	74	71
1.00	150	147	137	135	144	133	121	119	114	113	101	99	90	89	111	99	98	89	89	98	89	88	85
1.25	166	163	149	148	159	145	137	134	128	127	115	113	104	103	124	113	112	103	103	111	103	102	98
1.50	177	174	158	157	170	154	149	147	139	137	126	125	116	115	135	124	123	115	114	122	114	113	109
2.00	194	192	171	170	186	168	168	166	154	153	143	142	134	133	150	141	140	132	132	138	131	130	127
2.50	206	203	180	179	197	176	181	179	165	163	155	153	146	145	160	152	151	145	144	149	143	142	138
3.00	214	212	185	184	205	182	191	188	172	171	163	162	156	154	167	160	159	153	153	157	152	150	147
4.00	224	222	192	191	215	189	203	201	181	180	174	173	167	166	176	170	170	165	164	167	163	161	158
5.00	230	229	196	196	221	193	211	209	186	186	180	179	175	174	182	177	176	172	171	174	170	167	165
10.00	244	243	205	204	234	202	228	227	198	198	195	194	192	191	194	191	191	188	188	187	185	182	180
20.00	251	250	209	209	241	207	238	238	205	205	203	203	201	201	200	199	199	197	197	195	194	190	188

LM53 SHR C0-C180: 1.274 SHR C90-C270: 1.262 SHR Square: 1.396

<b>Luminaire</b>		<b>Measur.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm


Average Luminance [cd/m²]										
0.0°	45°	50°	55°	60°	65°	70°	75°	80°	85°	
2753	2772	2766	2771	2777	2833	3035	3350	3428	---	
90.0°	2742	2767	2800	2837	3016	3219	3306	3069	2657	---

Flush mounted or longitudinal view												
		Illumination(lx)										
A	A	2000	1000	750	500		<300					1.15
B	1		2000	1500	1000	750	500	<300				1.5
C					2000		1000	500	<300			1.85
D	2						2000	1000	500	<300		2.2
E	3							2000	1000	500	<300	2.55



<b>Luminaire</b>		<b>Measur.</b>		<b>Lamp</b>	
Code	5376	Code	5376	Code	PL-L24W/840/4P
Name	Ceiling lamp 50x30 no dim	Name	Ceiling lamp 50x30 no dim	Number	4
Line	VIBIA-Link	Date	29-05-2014	Position	Universal
Efficiency	19.62%	Coordinate system	CG	Total Flux	6000.00 lm

Luminance



Luminaire					Measurem.					Lamp				
Code	5376				Code	5376				Code	PL-L24W/840/4P			
Name	Ceiling lamp 50x30 no dim				Name	Ceiling lamp 50x30 no dim				Number	4			
Line	VIBIA-Link				Date	29-05-2014				Position	Universal			
Efficiency		19.62%			Coordinate system		CG			Total Flux		6000.00 lm		
Luminance cd/m2														
Table 1/3														
	C 0.00	C 10.00	C 20.00	C 30.00	C 40.00	C 50.00	C 60.00	C 70.00	C 80.00	C 90.00	C 100.00	C 110.00	C 120.00	
G 0.0	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	
G 5.0	2783.27	2780.49	2779.67	2779.69	2779.33	2778.89	2778.81	2778.85	2779.03	2779.32	2779.03	2778.85	2778.81	
G 10.0	2784.70	2779.24	2777.28	2776.89	2776.60	2775.75	2774.49	2774.62	2774.68	2773.97	2774.68	2774.62	2774.49	
G 15.0	2782.60	2774.83	2772.11	2771.63	2771.42	2771.05	2771.63	2773.39	2774.39	2774.78	2774.39	2773.39	2771.63	
G 20.0	2788.53	2773.40	2764.61	2762.52	2762.58	2764.43	2767.04	2768.19	2767.78	2766.48	2767.78	2768.19	2767.04	
G 25.0	2782.36	2765.57	2755.00	2752.73	2755.88	2757.81	2758.25	2757.76	2757.91	2758.70	2757.91	2757.76	2758.25	
G 30.0	2776.20	2752.34	2746.22	2747.51	2744.97	2743.36	2745.76	2746.73	2747.14	2748.05	2747.14	2746.73	2745.76	
G 35.0	2758.44	2729.58	2723.90	2733.85	2730.84	2729.34	2732.84	2734.17	2734.93	2736.72	2734.93	2734.17	2732.84	
G 40.0	2751.27	2728.49	2717.24	2717.06	2718.67	2724.44	2731.27	2730.32	2729.77	2729.62	2729.77	2730.32	2731.27	
G 45.0	2753.48	2729.40	2710.75	2701.52	2702.06	2704.28	2707.71	2718.55	2731.07	2741.75	2731.07	2718.55	2707.71	
G 50.0	2771.51	2726.40	2697.05	2688.21	2694.22	2711.34	2729.21	2736.60	2747.29	2766.94	2747.29	2736.60	2729.21	
G 55.0	2765.60	2711.08	2693.69	2691.93	2687.36	2706.65	2745.92	2764.45	2778.61	2800.33	2778.61	2764.45	2745.92	
G 60.0	2771.49	2699.00	2678.92	2700.43	2710.88	2738.36	2783.35	2809.10	2823.62	2837.28	2823.62	2809.10	2783.35	
G 65.0	2776.76	2713.05	2694.79	2724.73	2769.19	2818.03	2877.32	2951.46	3000.59	3015.87	3000.59	2951.46	2877.32	
G 70.0	2833.17	2747.98	2723.75	2776.31	2874.85	2981.75	3086.27	3190.20	3236.03	3218.67	3236.03	3190.20	3086.27	
G 75.0	3034.79	2914.06	2841.59	2888.24	3082.06	3201.94	3226.60	3322.61	3365.44	3305.53	3365.44	3322.61	3226.60	
G 80.0	3350.34	3123.32	3007.92	3028.34	3110.12	3125.35	3103.64	3106.22	3102.28	3068.58	3102.28	3106.22	3103.64	
G 85.0	3427.88	2839.54	2669.84	2683.80	2676.19	2646.72	2637.52	2717.26	2739.33	2657.17	2739.33	2717.26	2637.52	
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

Luminaire					Measurem.					Lamp			
Code	5376				Code	5376				Code	PL-L24W/840/4P		
Name	Ceiling lamp 50x30 no dim				Name	Ceiling lamp 50x30 no dim				Number	4		
Line	VIBIA-Link				Date	29-05-2014				Position	Universal		
Efficiency		19.62%			Coordinate system		CG			Total Flux		6000.00 lm	
Luminance cd/m2      Table 2/3													
	C 130.00	C 140.00	C 150.00	C 160.00	C 170.00	C 180.00	C 190.00	C 200.00	C 210.00	C 220.00	C 230.00	C 240.00	C 250.00
G 0.0	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46
G 5.0	2778.89	2779.33	2779.69	2779.67	2780.49	2783.27	2780.49	2779.67	2779.69	2779.33	2778.89	2778.81	2778.85
G 10.0	2775.75	2776.60	2776.89	2777.28	2779.24	2784.70	2779.24	2777.28	2776.89	2776.60	2775.75	2774.49	2774.62
G 15.0	2771.05	2771.42	2771.63	2772.11	2774.83	2782.60	2774.83	2772.11	2771.63	2771.42	2771.05	2771.63	2773.39
G 20.0	2764.43	2762.58	2762.52	2764.61	2773.40	2788.53	2773.40	2764.61	2762.52	2762.58	2764.43	2767.04	2768.19
G 25.0	2757.81	2755.88	2752.73	2755.00	2765.57	2782.36	2765.57	2755.00	2752.73	2755.88	2757.81	2758.25	2757.76
G 30.0	2743.36	2744.97	2747.51	2746.22	2752.34	2776.20	2752.34	2746.22	2747.51	2744.97	2743.36	2745.76	2746.73
G 35.0	2729.34	2730.84	2733.85	2723.90	2729.58	2758.44	2729.58	2723.90	2733.85	2730.84	2729.34	2732.84	2734.17
G 40.0	2724.44	2718.67	2717.06	2717.24	2728.49	2751.27	2728.49	2717.24	2717.06	2718.67	2724.44	2731.27	2730.32
G 45.0	2704.28	2702.06	2701.52	2710.75	2729.40	2753.48	2729.40	2710.75	2701.52	2702.06	2704.28	2707.71	2718.55
G 50.0	2711.34	2694.22	2688.21	2697.05	2726.40	2771.51	2726.40	2697.05	2688.21	2694.22	2711.34	2729.21	2736.60
G 55.0	2706.65	2687.36	2691.93	2693.69	2711.08	2765.60	2711.08	2693.69	2691.93	2687.36	2706.65	2745.92	2764.45
G 60.0	2738.36	2710.88	2700.43	2678.92	2699.00	2771.49	2699.00	2678.92	2700.43	2710.88	2738.36	2783.35	2809.10
G 65.0	2818.03	2769.19	2724.73	2694.79	2713.05	2776.76	2713.05	2694.79	2724.73	2769.19	2818.03	2877.32	2951.46
G 70.0	2981.75	2874.85	2776.31	2723.75	2747.98	2833.17	2747.98	2723.75	2776.31	2874.85	2981.75	3086.27	3190.20
G 75.0	3201.94	3082.06	2888.24	2841.59	2914.06	3034.79	2914.06	2841.59	2888.24	3082.06	3201.94	3226.60	3322.61
G 80.0	3125.35	3110.12	3028.34	3007.92	3123.32	3350.34	3123.32	3007.92	3028.34	3110.12	3125.35	3103.64	3106.22
G 85.0	2646.72	2676.19	2683.80	2669.84	2839.54	3427.88	2839.54	2669.84	2683.80	2676.19	2646.72	2637.52	2717.26
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire					Measurem.					Lamp			
Code	5376				Code	5376				Code	PL-L24W/840/4P		
Name	Ceiling lamp 50x30 no dim				Name	Ceiling lamp 50x30 no dim				Number	4		
Line	VIBIA-Link				Date	29-05-2014				Position	Universal		
Efficiency		19.62%			Coordinate system		CG			Total Flux		6000.00 lm	
Luminance cd/m2													
Table 3/3													
	C 180.00	C 190.00	C 200.00	C 210.00	C 220.00	C 230.00	C 240.00	C 250.00	C 260.00	C 270.00	C 280.00	C 290.00	C 300.00
G 0.0	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46	2780.46
G 5.0	2783.27	2780.49	2779.67	2779.69	2779.33	2778.89	2778.81	2778.85	2779.03	2779.32	2779.03	2778.85	2778.81
G 10.0	2784.70	2779.24	2777.28	2776.89	2776.60	2775.75	2774.49	2774.62	2774.68	2773.97	2774.68	2774.62	2774.49
G 15.0	2782.60	2774.83	2772.11	2771.63	2771.42	2771.05	2771.63	2773.39	2774.39	2774.78	2774.39	2773.39	2771.63
G 20.0	2788.53	2773.40	2764.61	2762.52	2762.58	2764.43	2767.04	2768.19	2767.78	2766.48	2767.78	2768.19	2767.04
G 25.0	2782.36	2765.57	2755.00	2752.73	2755.88	2757.81	2758.25	2757.76	2757.91	2758.70	2757.91	2757.76	2758.25
G 30.0	2776.20	2752.34	2746.22	2747.51	2744.97	2743.36	2745.76	2746.73	2747.14	2748.05	2747.14	2746.73	2745.76
G 35.0	2758.44	2729.58	2723.90	2733.85	2730.84	2729.34	2732.84	2734.17	2734.93	2736.72	2734.93	2734.17	2732.84
G 40.0	2751.27	2728.49	2717.24	2717.06	2718.67	2724.44	2731.27	2730.32	2729.77	2729.62	2729.77	2730.32	2731.27
G 45.0	2753.48	2729.40	2710.75	2701.52	2702.06	2704.28	2707.71	2718.55	2731.07	2741.75	2731.07	2718.55	2707.71
G 50.0	2771.51	2726.40	2697.05	2688.21	2694.22	2711.34	2729.21	2736.60	2747.29	2766.94	2747.29	2736.60	2729.21
G 55.0	2765.60	2711.08	2693.69	2691.93	2687.36	2706.65	2745.92	2764.45	2778.61	2800.33	2778.61	2764.45	2745.92
G 60.0	2771.49	2699.00	2678.92	2700.43	2710.88	2738.36	2783.35	2809.10	2823.62	2837.28	2823.62	2809.10	2783.35
G 65.0	2776.76	2713.05	2694.79	2724.73	2769.19	2818.03	2877.32	2951.46	3000.59	3015.87	3000.59	2951.46	2877.32
G 70.0	2833.17	2747.98	2723.75	2776.31	2874.85	2981.75	3086.27	3190.20	3236.03	3218.67	3236.03	3190.20	3086.27
G 75.0	3034.79	2914.06	2841.59	2888.24	3082.06	3201.94	3226.60	3322.61	3365.44	3305.53	3365.44	3322.61	3226.60
G 80.0	3350.34	3123.32	3007.92	3028.34	3110.12	3125.35	3103.64	3106.22	3102.28	3068.58	3102.28	3106.22	3103.64
G 85.0	3427.88	2839.54	2669.84	2683.80	2676.19	2646.72	2637.52	2717.26	2739.33	2657.17	2739.33	2717.26	2637.52
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00